

E-2.1 Environmental scenario for generic industrial use of borates resulting in the manufacture of another substance

Systematic title based on use descriptor	ERCs	Description
	1	Manufacture of chemicals
	6a	Industrial use resulting in manufacture of another substance (use of intermediates)
	6b	Industrial use of reactive processing aids
Sub scenarios		ES1: Default dilution ES2: Dilution of 100

E-2.2 Controlling environmental exposure

Product characteristics	Granular, powder or dissolved form		
Amounts used	ES1: 190 T B/y	ES2: 1 150 T B/y	
Frequency and duration of use	300 days per year		
Environment factors not influenced by risk management	ES1: Dilution of 10	ES2: Dilution of 100	
Other given operational conditions affecting environmental exposure	Delivery and raw material handling mostly happen in open air. Weighing takes place inside. Most of the subsequent steps take place inside a building in (semi) enclosed systems.		
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	Release factor to water after on-site treatment	ES1: 60 000 g/T	ES2: 60 000 g/T
	Release factor to air after on-site treatment	ES1: 36 562 g/T	ES2: 36 562 g/T
Organizational measures to prevent/limit release from site	Spillages of powder or granulated borates should be swept or vacuumed up immediately and placed in containers for disposal in order to prevent unintentional release to the environment.		
Conditions and measures related to municipal sewage treatment plant	Not relevant, boron is not removed from water in municipal STP. If sites discharge to a municipal STP the concentration of boron should not exceed 10 mg/L in the municipal STP.		
Conditions and measures related to external treatment of waste for disposal	Where appropriate material should be recovered and recycled through the process. Waste containing borates should be handled as hazardous waste.		

E-2.3. Exposure estimation

ES1: Environmental Exposure Estimations	Environment	PEC	PNECadd	RCR	
		Aquatic environment	1 956 µg/L	2 020 µg/L	0.969
Terrestrial environment	0.86 mg/kg dw	5.4 mg/kg dw	0.158		
ES2: Environmental Exposure Estimations	Environment	PEC	PNECadd	RCR	
		Aquatic environment	1 206 µg/L	2 020 µg/L	0.597
		Terrestrial environment	5.15 mg/kg dw	5.4 mg/kg dw	0.954

E-2.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

The DU works inside the boundaries set by the ES if either the proposed risk management measures or emissions (expressed in g/T) as described above are met or the DU can demonstrate on his own that his implemented risk management measures or emissions are adequate. Detailed guidance for evaluation of ES can be acquired via your supplier or from the ECHA website (guidance R16). For environmental exposure, a DU-scaling tool (free download: <http://www.arche-consulting.be/Metal-CSA-toolbox/du-scaling-tool>) is available.